






Granulation method

Bibliographic data	Description	Claims	Mosaics	Original document	INPADOC LEGAL status
Patent number:	DE19844523				
Publication date:	2000-03-30				
Inventor:	LARSON BERND (DE); MARKIEFKA JOSEF (DE); RAEHSE WILFRIED (DE); SCHULZE WIELAND (DE); SUNDER MATTHIAS (DE)				
Applicant:	HENKEL KGAA (DE)				
Classification:					
- international:	B01J2/10; C11D1/04; C11D1/14; C11D1/22; C11D3/04; C11D3/08; C11D3/10; C11D3/12; C11D3/37; C11D10/02; C11D11/00; C11D11/04; C11D17/06; B01J2/10; C11D1/02; C11D3/04; C11D3/08; C11D3/10; C11D3/12; C11D3/37; C11D10/00; C11D11/00; C11D11/04; C11D17/06; (IPC1-7): C11D17/00; C11D1/83				
- european:	C11D1/22; C11D11/04; C11D17/06H				
Application number:	DE19981044523 19980929				
Priority number(s):	DE19981044523 19980929				
View INPADOC patent family					
Report a data error here					
Abstract of DE19844523 <p>The invention relates to a neutralization and granulation method. According to said method, a neutralizing foam is used as granulation adjuvant. Said neutralizing foam was previously obtained by mixing an anionic surfactant in its acid form, which was expanded using a gaseous medium, and a highly concentrated, aqueous alkaline component, which was expanded using a gaseous medium. The neutralizing foam has an average pore size of less than 10 mm, preferably less than 5 mm and especially less than 2 mm.</p>					
Data supplied from the esp@cenet database - Worldwide					

Also published as:

-  WO0018872 (A1)
-  EP1123382 (A1)
-  US6468957 (B1)
-  EP1123382 (A0)
-  EP1123382 (B1)
- more >>

BEST AVAILABLE COPY